



4 CHANNEL COMPRESSOR DE-ESSER

DPR-404

LINK IN

MASTER 1

BELOW TH GAIN REDUCTION

-20 10 0 5 TH 20 30 10 12 0 0 1

NORM ATTACK RELEASE

FAST

4k 6k 8k 2k 1k 10k

8 6 4 2

MAX OUT

FREQ DE-ESS

-10 -5 0

-30 dBu OUT

4 6 8

2 0

OUT RATIO

-10 0 +10

-20 dB GAIN

THRESHOLD

LINK IN

MASTER 2

BELOW TH GAIN REDUCTION

-20 10 0 5 TH 20 30 10 12 0 0 1

NORM ATTACK RELEASE

FAST

4k 6k 8k 2k 1k 10k

8 6 4 2

MAX OUT

FREQ DE-ESS

-10 -5 0

-30 dBu OUT

4 6 8

2 0

OUT RATIO

-10 0 +10

-20 dB GAIN

THRESHOLD

LINK IN

MASTER 3

BELOW TH GAIN REDUCTION

-20 10 0 5 TH 20 30 10 12 0 0 1

NORM ATTACK RELEASE

FAST

4k 6k 8k 2k 1k 10k

8 6 4 2

MAX OUT

FREQ DE-ESS

-10 -5 0

-30 dBu OUT

4 6 8

2 0

OUT RATIO

-10 0 +10

-20 dB GAIN

THRESHOLD

LINK IN

MASTER 4

BELOW TH GAIN REDUCTION

-20 10 0 5 TH 20 30 10 12 0 0 1

NORM ATTACK RELEASE

FAST

4k 6k 8k 2k 1k 10k

8 6 4 2

MAX OUT

FREQ DE-ESS

-10 -5 0

-30 dBu OUT

4 6 8

2 0

OUT RATIO

-10 0 +10

-20 dB GAIN

THRESHOLD