



- 1 0.00076[.000030] MIN GOLD IN CONTACT AREA, 0.00381[.000150] MIN TIN-LEAD ON SOLDER TAILS ALL OVER 0.00127[.000050] MIN NICKEL
- 2 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- 3 PARTS TO BE PACKAGED IN TUBES.
- 4 PARTS TO BE PACKAGED IN TAPE AND REEL.
- 5 KAPTON VACUUM PICK-UP BUTTON FOR -2 & -4 ONLY (SHOWN IN PHANTOM TO SHOW CONNECTOR DETAIL).
- 6 0.00076[.000030] MIN GOLD IN CONTACT AREA, 0.00381[.000150] MIN TIN ON SOLDER TAILS ALL OVER 0.00127[.000050] MIN NICKEL

6	4	AS SHOWN	1,13,38, 50	ALL OTHER PINS	25,26	146839-4
6	3					146839-3
1	4					146839-2
1	3					146839-1
CONTACT FINISH	PACKAGING	DESCRIPTION	.197	.167	.138	ASSEMBLY PART NUMBER
			"L" PIN LGTH & CAVITY LOCATION			

THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN J.ROOT	27JUN96	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm [INCHES]		CHK V. RUMINSKI	07MAR07	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD		PRODUCT SPEC	
0 PLC ± -				APPLICATION SPEC	
1 PLC ± -				SIZE	
2 PLC ± 0.13[.005]				CAGE CODE	
3 PLC ± -				DRAWING NO	
4 PLC ± -				SCALE	
ANGLES ± 2°				SHEET	
MATERIAL HOUSING: LCP, BLACK		FINISH SEE TABLE		WEIGHT	
		CUSTOMER DRAWING		SCALE 4:1	
				SHEET 1 OF 1	
				REV D1	